

Bemessungshilfe

Diese Tabelle ersetzt keine statische Berechnung!

Produkt: Brettschichtholz GL 24 (BS 11)

SCHMELTER

KVH®, BSH, DUO-/TRIO-BALKEN, BAUHOLZ

Belastung kN/mU Stützweite/m	0,5	1,1	2,0	2,5	3,0	4,0	5,0	6,0	7,0	8,0	9,0	10,0
2,0			6/14		6/16	6/18	6/20	8/16	8/18	8/18	8/20	8/20
			8/10		8/12	8/14	8/16	10/14	10/14	10/16	10/16	10/20
			10/10		10/12	10/12	10/12	12/12	12/14	12/14	12/16	12/16
3,0	6/12	8/12	8/16	8/16	10/16	8/20	8/24	8/24	8/24	10/24	10/24	10/28
		6/14	10/14		12/16	10/20	10/20	10/20	10/24	14/20	14/20	12/24
			12/14		14/14	12/16	12/20	12/20	12/20	16/20	16/20	16/20
4,0	8/12	8/16	8/20	10/20	10/24	8/24	10/24	10/28	10/28	14/28	12/32	12/32
	6/14		10/20		12/20	10/24	12/24	12/24	14/24	16/24	14/28	14/28
			12/20		14/20	14/20	14/24	14/24	16/24	18/24	18/24	16/28
5,0	8/16	8/20	10/24	12/24	12/24	10/28	12/32	12/32	12/32	12/36	12/36	14/36
			12/24		14/24	12/28	14/28	16/28	16/32	14/32	14/36	16/36
			14/20		16/24	16/24	16/28	18/28	18/28	16/32	16/32	18/32
6,0	8/18	8/24	10/28	12/28	14/28	12/32	12/36	12/36	14/36	16/36	16/40	16/40
			14/24		16/28	14/32	14/36	14/36	16/36	18/36	18/36	18/40
			16/24		18/26	18/28	16/32	18/32	18/36	20/36	20/36	20/36
7,0	10/20	12/24	12/32	12/32	12/36	14/36	14/40	16/40	16/40	16/44	16/44	18/44
			14/28		14/32	16/36	16/36	18/40	18/40	18/44	18/44	20/44
			16/28		16/32	18/32	18/36	20/36	20/40	20/40	20/44	
8,0	14/20	14/28	14/32	14/36	14/40	16/40	16/44	16/44	18/44			
	8/24		16/32		16/36	18/40	18/40	18/44	20/44			
			18/32		20/32	20/36	20/40	20/44				
9,0	12/24	12/32	14/36	16/40	16/40	16/44	20/44					
			20/32		18/40	18/44						
					20/36	20/40						
10,0	10/28	16/32	16/40	20/44	16/44							
			20/36		18/44							
					20/40							